

CO2 concentration transmitter with RS485 and two relay outputs





CO2 level transmitter with two output relays.

Green LED shines - CO2 concentration 0 to 1000 ppm

Yellow LED shines - CO2 concentration 1001 to 1200 ppm

Red LED shines - CO2 concentration 1201 ppm and more

Extended measuring range available for an additional charge

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Technical data

| CO2 SENSOR | |
|------------------------|---|
| Measuring range | 0 to 5000 ppm |
| Accuracy | ±(50ppm +3% from reading) at 25°C and 1013hPa |
| Resolution | 1 ppm |
| RELAY OUTPUTS | |
| Quantity | 2 |
| Maximal voltage | 50 V |
| Maximal current | 2 A |
| Maximal power | 60 VA |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +60 °C |
| Channels | internal CO ₂ sensor |
| Acoustic alarm | from built-in beeper - switchable |
| Output | RS485 |
| Communication protocol | ModBus RTU and Advantech ADAM compatible protocol |
| Power | 9-30 Vdc |
| Protection class | IP30 |
| Dimensions | 136 x 150 x 45 mm |
| Weight | approx. 360 g |

| Warranty | 3 years |
|----------|---------|