Web Sensor - two channel remote 0-20mA inputs



code: P2520

Dual channel p-line Web Sensor from 0-20mA (4-20mA) to Ethernet.
Remote alarm.
Easy wireless communication **using Web Sensor and optional** Wireless TP-LINK router**.**

Processing and analysis of measured data:

- online in COMET Cloud
- COMET Database software
- integration into 3-party systems

With a newly purchased WebSensor with Ethernet communication, you receive 3 months of COMET Cloud. for free; a full year of operation in COMET Cloud. then requires 1 credit.

Technical data

CURRENT INPUT	
Accuracy proudu	±0.1% FS od 0 °C do +50 °C ±0.3% FS od -30 °C do +80 °C
Resolution	1 µA
A/D converter resolution	24bit sigma-delta
Input resistance	20 Ω
Measuring interval	1 s
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	2x proudový vstup
Output	Ethernet
Measuring interval	1 s
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc
Protection class	IP30
Dimensions	88 x 126 x 39,5 mm
Weight	approx. 150 g
Warranty	3 years