

Temperature and humidity regulator with RS232 output, cable 4 meters

code: H3331-4



Humidistat, thermostat with two relay outputs. Outdoor, indoor use.
 Relative humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy. Three two-state inputs.

The device is supplied with T+RH probe with 4 meters cable.

Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +105 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
RELAY OUTPUTS	
Quantity	2
Maximal voltage	50 V
Maximal current	2 A
Maximal power	60 VA
BINARY INPUTS	
Quantity	3
Signal for binary inputy	dry contact, open collector or two-state voltage signal. Inputs are not galvanically isolated.
Minimum pulse duration on binary input	500 ms
Voltage across open contact	< 3,3 V
Low voltage level	0 to +0,5 V
High voltage level	+3,0 to +30 V
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C

Channels	1x connectable temperature+humidity probe
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Acoustic alarm	from built-in beeper - switchable
Output	RS232
Range of humidity sensor temperature compensation	all temperature range
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	ModBus RTU and Advantech ADAM compatible protocol
Power	9-30 Vdc
Protection class	IP65 electronics; IP40 sensors
Dimensions	136 x 159 x 45 mm; length/diameter of external probe 88/18 mm
External probe cable length	4 meters
Weight	approx. 500 g
Warranty	3 years